

UTYL

Lighting points


PCL09507 Square single lighting point 4 m / 2 334 lm - 17.8 W
PCL09508 Square single lighting point 5 m / 2 334 lm - 17.8 W

Use

Lighting points for minor roads, pathways, cycle paths and around buildings.



Asymmetrical flat beam



Light distribution 17.8 W

LED light 17.8 W

Masthead luminaire with asymmetrical flat beam light distribution. Supplied with connection cable X05BQ-F 4x1², cable length 8 m. LED power supply unit 220-240 V - 0/50-60 Hz - DC 176-264 V - DALI controllable. Luminaire made of aluminium alloy, aluminium and stainless steel. Safety glass, antireflection-coated. Silicone gasket. Reflector surface made of pure aluminium. Dust-tight and protection against strong water jets. Safety class II Safety mark **CE** Conformity mark Impact strength IK07 Protection class IP 66 Luminous flux upper half-space: 0% CIE/CEN flux code: 33 67 95 100 100 BUG-Rating: B1 U0 G1

Lamp

Luminaire connected wattage 17.8 W
 Luminous luminous flux 2 334 lm
 Luminous luminous efficiency 131.1 lm/W
 Colour temperature* 3 000 K (CRI > 80)
 Ambient temperature $t_{a,max} = 50^{\circ}\text{C}$
 ✓ Complies with light pollution legislation (27 Dec 2018)
 20-year LED module availability guarantee.
 *Other colour temperatures on request.


Other configurations available

Luminaire with asymmetric light distribution.
 Twin luminaire or side-mounted luminaire.

Luminaire colour

Graphite
 Silver

Alternative finishes and salt air protection on request.



Utyl - Lighting points 4-5 m - 17.8 W
 Utyl - Lighting points 5-6 m - 33.5 W
 Utyl - Lighting points 6-7-8 m - 51.2 W
 Utyl - Lighting points 7-8 m - 67 W

Square shaft

Regular square shaft in glued laminated timber GL24H certified ACERBOIS GLULAM, produced with sawn planks from sustainably managed forests and respecting HTE process. Timber finished with four coats of woodstain. Square flush base in galvanized steel and polyester powder coated finish. Overlying top in pressed galvanized steel, polyester powder coated finish. Design and manufacture according to rules defined by DEE 120017-00-0106 Wood and metal lighting columns and specifications from European Technical Approval ETA-18/0016. CE marked product: Conformity certificate CE 0679-CPR-0473.

Standard finishes

Wood: Brume
 Metal: Black 2100 sanded
 Finish corresponding to the references PCL09507 and PCL09508. Other colours on request.

Benefits

- scots pine heartwood selected
- non-chemically treated wood
- design according to the HTE (High Strength Outdoor) process based on the principle of a shaft reconstituted from four glued laminated timber planks by a double cross-lamination process and guaranteeing a high outdoor performance of the product.

Lifespan

According to our raw material supply specifications and the CSTB, our products have a structural life of 25 years (CE marking).

Maintenance

In order to maintain the performance of the columns and their aesthetics, it is advisable to plan periodic maintenance every 7 years (5 years on sites exposed to the sea front) by renewing the finish. This operation does not require any particular expertise or removal of the columns. Aubrilam can assist you in this process by providing its products, application protocol or technical staff (see the chapter on Wood/Maintenance).

Installation

Luminaire delivered without case, light head not assembled on the shaft. Possibility of mounting the luminaire on a bracket or on a wall on request. Fixing with 4 HA20/M18 - 400 mm. The lighting fixture must be connected to the earth of the base section thanks to the green/yellow wire provided for that purpose. Anchor bolts supplied on request only.

Technical data can be viewed and downloaded from our website.



	LED	A	B	C	D	E x F	P	G	H	J	K	L	KG
PCL09507	17.8 W	4 m	120 mm	120 mm	100 mm	300 x 80 mm	0.35 m	120 mm	1 m	271 x 271 mm	200 x 200 mm	4 HA20/M18 - 400 mm	30 kg
PCL09508	17.8 W	5 m	120 mm	120 mm	100 mm	300 x 80 mm	0.35 m	120 mm	1.20 m	271 x 271 mm	200 x 200 mm	4 HA20/M18 - 400 mm	35 kg

A. Pole height / B. Shaft section at base / C. Shaft section on top / D. Door: Effective depth / E x F. Door: Effective height x width / P. Distance door bottom to plate / G. Base section / H. Base height / J. Base plate dimensions / K. Spacing dimensions / L. Anchor bolts / KG. Wooden pole weight.